

APC BX1100LI-MS UPS (1100VA, 230V, AVR)

PRD-202607-0046 · APC · Specification Sheet

Brand	APC
Model / MPN	BX1100LI-MS
Reference price	MYR 719.00 (reference only)
Type	UPS

APC BX1100LI-MS UPS

1100VA | 230V | AVR

Warranty
- 2 year Manufacturer Limited Warranty ([APC Service Center](#))

SPECIFICATIONS

Specifications

Model	BX1100LI-MS
Output	<p>Output power capacity: 550 Watts / 1.1 kVA</p> <p>Max Configurable Power (Watts): 550 Watts / 1.1 kVA</p> <p>Nominal Output Voltage: 230V</p> <p>Output Frequency (sync to mains): 50/60 Hz +/-1 Hz</p> <p>Output Frequency (not synced): 50/60 Hz +/-1 Hz</p> <p>Topology: Line Interactive</p> <p>Waveform type: Stepped approximation to a sine wave</p> <p>Output Connections: (2) IEC 320 C13 (Battery Backup)</p> <p>Transfer Time: 4ms typical : 6ms maximum</p>
Input	<p>Nominal Input Voltage: 230V</p> <p>Input frequency: 50/60 Hz +/- 3 Hz (auto sensing)</p> <p>Input Connections: IEC-320 C14, NEMA 5-15P</p> <p>Cord Length: 1.22 meters</p> <p>Input voltage range for main operations: 150 - 280 V</p> <p>Number of Power Cords: 1</p> <p>Type of Input Protection Required: 3-pole breaker</p> <p>Maximum Input Current: 10.0 A</p> <p>Input Power Factor at Full Load: 0.5</p>
Batteries & Runtime	<p>Battery type: Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof</p> <p>Included Battery Modules: 1</p> <p>Typical recharge time: 6 hour(s)</p> <p>Replacement Battery: RBC17</p> <p>Battery Volt-Amp-Hour Capacity: 96</p>
Communications & Management	<p>Control panel: LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators</p> <p>Audible Alarm: Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm</p>

