

APC CS 650VA BK650-AS Battery Backup UPS

PRD-202607-0049 · APC · Specification Sheet

Brand	APC
Model / MPN	BK650-AS
Reference price	MYR 895.00 (reference only)

APC CS 650VA BK650-AS Battery Backup UPS

650VA, 400W | Input & Output 230V | Protection for Computers | USB Interface

Warranty

- 2 years Manufacturer Limited Warranty

Specifications

Specifications	
Model	APC Back-UPS CS 650VA BK650-AS Battery Backup UPS
Output	Output Power Capacity-400 Watts / 650 VA Max Configurable Power-400 Watts / 650 VA Nominal Output Voltage-230V Output Connections-(1) IEC 320 C13 (Surge Protection), (3) IEC 320 C13 (Battery Backup)
Input	Nominal Input Voltage-230V Input Frequency-50/60 Hz +/- 3 Hz (auto sensing) Input Connections-IEC-320 C14 Cord Length-1.83 meters Input voltage range for main operations-180 - 260V Input voltage adjustable range for mains operation-160 - 282V
Batteries & Runtime	Battery Type-Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof Typical recharge time-8 hour(s) Replacement Battery-RBC17 RBC Quantity-1
Communications & Management	Interface Port(s)-USB Control panel-LED status display with On Line : On Battery : Replace Battery and Overload indicators Audible Alarm-Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	Surge energy rating-320 Joules Data Line Protection-Analog phone line for phone/fax/modem/DSL (RJ-45 connector)
Color	Beige
Environmental	Operating Environment-0 - 40 °C Operating Relative Humidity-5 - 95% Operating Elevation-0-9000 meters Storage Temperature:-15 - 45 °C Storage Relative Humidity-5 - 95% Storage Elevation-0-4500 meters Audible noise at 1 meter from surface of unit-45.00 dBA Online Thermal Dissipation-0.00 BTU/hr
Regulatory Approvals	A-tick,C-tick,CE,GOST,NEMKO
Dimension	91 mm (W) × 165 mm (H) × 284 mm (D)
Weight	6.04kg

* Features, Package Content and Specifications are subject to change without prior notification.*

