

APC BX950U-MS UPS (950VA, 230V, AVR)

PRD-202607-0051 · APC · Specification Sheet

Brand	APC
Model / MPN	BX950U-MS
Reference price	MYR 899.00 (reference only)
Type	UPS

APC BX950U-MS UPS

950VA | 230V | AVR

Warranty

- 2 year Manufacturer Limited Warranty ([APC Service Center](#))

SPECIFICATIONS

Specifications

Model	BX950U-MS
Output	<p>Output power capacity: 480 Watts / 950 VA</p> <p>Max Configurable Power (Watts): 480 Watts / 950 VA</p> <p>Nominal Output Voltage: 230V</p> <p>Output Frequency (sync to mains): 50/60 Hz +/-1 Hz</p> <p>Output Frequency (not synced): 50/60 Hz +/-1 Hz</p> <p>Topology: Line Interactive</p> <p>Waveform type: Stepped approximation to a sine wave</p> <p>Output Connections: (2) IEC 320 C13 (Battery Backup)</p> <p>Transfer Time: 8ms typical : 10 ms maximum</p>
Input	<p>Nominal Input Voltage: 230V</p> <p>Input frequency: 50/60 Hz +/- 3 Hz (auto sensing)</p> <p>Input Connections: IEC-320 C14, NEMA 5-15P</p> <p>Cord Length: 1.22 meters</p> <p>Input voltage range for main operations: 150 - 280 V</p> <p>Number of Power Cords: 2</p> <p>Type of Input Protection Required: 3-pole breaker</p> <p>Maximum Input Current: 4.0 A</p>
Batteries & Runtime	<p>Battery type: Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof</p> <p>Included Battery Modules: 1</p> <p>Typical recharge time: 8 hour(s)</p> <p>Replacement Battery: RBC17</p> <p>Battery Volt-Amp-Hour Capacity: 76</p>
Communications & Management	<p>Interface Port(s): USB</p> <p>Control panel: LED status display with On Line : On Battery : Replace Battery and Overload indicators</p> <p>Audible Alarm: Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm</p>

